

## Electric Series Scissor Lifts

# 0608E(2132E)/0808E(2732E)/0612E(2146E)

Complies with ISO/CE/ANSI/AS/CU-TR/KCS standards

Model	0608E (2132E)		0808E (2732E)		0612E (2146E)		
	Metric	US	Metric	US	Metric	US	
Dimensions							
Max Working Height	8.3m	27'3"	10.1m	33'2"	8.3m	27'3"	
A Max Platform Height	6.3m	20'8"	8.1m	26'7"	6.3m	20'8"	
B Max Horizontal Extension	0.9m	3'	0.9m	3'	0.9m	3'	
C Length-Stowed	2.46m	8'	2.46m	8'	2.45m	8'	
D Width-Stowed	0.83m	2'8.7"	0.83m	2'8.7"	1.17m	3'10"	
Height-stowed	Rail Folded	1.84m	6'	1.96m	6'5"	1.6m	5'3"
	E Rail Unfolded	2.24m	7'4"	2.36m	7'9"	2.22m	7'3"
F Wheelbase	1.88m	6'2"	1.88m	6'2"	1.88m	6'2"	
Ground Clearance (Pothole Guard Stowed)	0.1m	4"	0.1m	4"	0.1m	4"	
Ground Clearance (Pothole Guard Deployed)	25mm	0.98"	25mm	0.98"	25mm	0.98"	
Platform Dimensions(L×W×H)	2.30m×0.8m×1.1m (7'6.5"×2'7.5"×3'7")		2.30m×0.8m×1.1m (7'6.5"×2'7.5"×3'7")		2.30m×1.15m×1.1m (7'6.5"×3'9"×3'7")		
<b>Performance</b>							
Platform Allowable Occupants (Indoor/Outdoor)	2 persons/1 person		2 persons/-		2 persons/2 persons		
Platform Capacity	380kg	838lbs	250kg	551lbs	550kg	1213lbs	
Drive Speed-Stowed	4km/h	2.5mph	4km/h	2.5mph	4km/h	2.5mph	
Drive Speed-Raised	0.8km/h	0.5mph	0.8km/h	0.5mph	0.8km/h	0.5mph	
Elevation Time(Unloaded)	25s~30s		30s~35s		33s~38s		
Descent Time(Unloaded)	30s~35s		34s~39s		30s~35s		
Gradeability	25%		25%		25%		
Turning Radius(Inside/Outside)	0/2.1m		0/2.1m		0/2.35m		
Tilt Rating(Front to Back/Side to Side)	3°/1.5°		3°/1.5°		3°/1.5°		
Tyres-solid	380×125mm(15×5")		380×125mm(15×5")		380×125mm(15×5")		
<b>Power</b>							
Batteries	6V×4/225Ah		6V×4/225Ah		6V×4/240Ah		
Power Source	24V DC		24V DC		24V DC		
Drive Mode	Motor, front-wheel		Motor, front-wheel		Motor, front-wheel		
Charger Input	100~240V AC		100~240V AC		100~240V AC		
Charger Output	30A		30A		30A		
Hydraulic System Capacity	15L	3.3gal	15L	3.3gal	19L	4.2gal	
<b>Weight</b>							
Weight	2,090kg	4,608lbs	2,265kg	4,994lbs	2,455kg	5,412lbs	
			Indoor only				
Standards Compliance	ISO/CE/ANSI/CSA/AS/CU-TR/KCS						

